

DP-520



Small and Light

For the ultimate in portability, the DP-220 is a great package to supply your mobile printer needs. SO small and light, you will hardly notice you are carrying it.

Provides the Connectivity and Compatibility You Need

If its a wired or wireless connection you need, the DP-2200 is capable of both. With RS232 serial and a serial/Bluetooth model, the choices available are sure to fit your requirement.

Highlights at a glance:

- Simple to use...single-hand, easy paper load system
- Ultra-portable size with the smallest footprint - weighs only 16-ounces, with battery and media
- Linerless label capability to reduce waste - more labels per roll
- Variety of mounting options - belt clip, wall mount, cart mount, vehicle mount

Ease of Use

Easy to operate with just one button, this printer can be operated with minimal training.

Paper loading is drop in and receipts are easy to tear off as they are printed.

Cost Effective

Return your investment many times over in a short time period with this low cost printer

Configurations:

- Serial
- Serial w/Bluetooth

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

DP-520

Print Method	Direct Thermal
Resolution	203 dpi (8 dots mm)
Print Speed	Up to 2.0 ips
Fonts	Fonts: 7 x 24, 10 x 24. Font Editor Utility software enables customization of character fonts by the user
Character Set	IBM® 224 character set, CP437
Standard Connectivity	RS232 Serial (RJ12 connector)
Optional Connectivity	Bluetooth
Emulations	Epson ESC POS printer language
Drivers	Win98, WinNT, Win2k, WinXP, WIN 7
Utilities	Remote Printer Setup Program provides convenient configuration via a Windows interface from any computer
Paper Roll Size	Maximum roll diameter 2.16" (57.5 cm), roll widths to 2.26" (55 mm)
Roll Capacity	Approximately 124' (37.7 m)
Roll Type	Accepts paper with and without core
Battery Type	Rechargeable 5-cell NiMH (6V, 1800 mAh)
Regulatory Approvals	CE mark, UL-listed AC adapters, E-mark on in-vehicle adapters, AJA
Physical Weight	1.0 lbs (446g) with battery and paper
Physical Size (L x W x H)	7.0" x 5.8" x 3.3" (17.8 x 14.8 x 3.3 cm)
Power Voltage	120 - 240 V wide range auto-sensing
Operating Temperature	32°F to 122°F (0°C to 50°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Humidity	10% to 90% RH (noncondensing)
MTBF	>13 million print lines (approximately 3,500 paper rolls)
Options:	AC Trickle Charger, 120 to 240 VAC
	In-Vehicle Trickle Charger, 12 to 24 VDC
	Belt Clip
	D9 to RJ12 Data Cable with jack socket for alternate charging
	Environmental Case
	Spare Batteries in Multipacks

DASCOM Americas

113 Mill Place Parkway

Verona, VA 24482

Phone 877-434-1377— Fax: 540-242-7221

www.dascomamericas.com

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS